UL Rated 6-A:80-B:C





Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro 20 MP unit is fitted with a pressure gauge that provides at-a-glance status, cylinder is manufactured from impact resistant steel and the valve assembly is all metal.



At a Glance

- Model Pro 10 TCM-9
- Multipurpose Dry Chemical
- UL listed
- UL rated 6-A:80-B:C
- Supplied with wall hanger
- Monoammonium Phosphate6 year limited warranty
- Suitable for use on most common fires

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- · Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 18 lb. of fire extinguishing agent (Average)
 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G)
 approved when fitted with mounting bracket (not supplied)
- Powder coated cylinder for corrosion protection
- U.S.C.G. approved bracket part number 292474



Pt # 466206 - 1 pack UPC: 0-47871-66206-7 I2F - 20047871662061

Product Specification

For use on the following

types of fire:

•	
Net agent weight (Average)	18 lb.
Unit weight (Average)	30 lb.
Diameter	7.0 inches
Height	21.6 inches
Discharge time	19-22 seconds
Discharge range	20 feet
Operating pressure	195 psi
Cylinder	Mild steel
Valve, handle, lever	Metal
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options



Packaging dimensions (inches)

5 5	,	,	
	Depth	Width	Height
Carton	7.5	7.5	21.75

