

# SAFETY DATA SHEET

## 1. Identification

Attack!® Super Off **Product identifier** 

Other means of identification

0301053 **Sold as Item** #S-3451 **Product code** 

**Recommended use** Solvent **Recommended restrictions** None known.

**Manufacturer** Quest Safety Products Inc.

1414 S. West St., Suite #200 Indianapolis, IN 46225

US

Information (800) 878-4872 Emergency (317) 781-4400

# 2. Hazard(s) identification

**Physical hazards** Flammable liquids Category 4 **Health hazards** Acute toxicity, oral Category 4 Acute toxicity, dermal Category 3 Carcinogenicity Category 1B Category 2

**Environmental hazards** Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment,

long-term hazard

**OSHA** defined hazards Not classified.

**Label elements** 



Signal word Danger

**Hazard statement** 

H227 Combustible liquid. Harmful if swallowed. H302 Toxic in contact with skin. H311 May cause cancer. H350 Toxic to aquatic life. H401

Toxic to aquatic life with long lasting effects. H411

**Prevention** P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response P301 + P312 - If swallowed: Call a poison center/doctor if you feel unwell.

P302 + P350 - If on skin: Wash with plenty of water.

P308 + P313 - If exposed or concerned: Get medical advice/attention.

P330 - Rinse mouth.

P361 + P364 - Take off immediately all contaminated clothing and wash it before reuse.

Category 2

P370 + P378 - In case of fire: Use appropriate media to extinguish.

P391 - Collect spillage.

**Storage** P403 + P235 - Store in a well-ventilated place. Keep cool.

**Disposal** P501 - Dispose of contents/container in accordance with local/regional/national/international

regulations.

# 3. Composition/information on ingredients

#### **Mixtures**

981 Version #: 01 Issue date: 06-03-2014

Product: Attack!® Super Off

Material name: S-3451 SOLVENT BLEND

Emergency Phone: 317-781-4400

Chemical name C	ommon name and synonyms	CAS number	%
Heavy Aromatic Naphtha		64742-94-5	70-90
1,2,4-Trimethylbenzene		95-63-6	0.1-10
2-Butoxyethanol		111-76-2	0.1-10
Naphthalene		91-20-3	0.1-10
Nonylphenol Ethoxylate		9016-45-9	0.1-10
Non-hazardous and other components below	reportable levels		0.1-10

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

**Inhalation** If overexposure to vapors or mist, move to fresh air. Call a physician if breathing becomes difficult.

Take off immediately all contaminated clothing. Wash off with soap and plenty of water. Call a Skin contact

POISON CENTER or doctor/physician if you feel unwell. Get medical attention if irritation develops

and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

**Indication of immediate** medical attention and special treatment needed

**Ingestion** 

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Take off immediately all contaminated clothing. IF exposed or concerned: Get medical **General information** advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take

precautions to protect themselves. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

**Unsuitable extinguishing** Do not use water jet as an extinguisher, as this will spread the fire. media

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/aii

**Special protective equipment** 

mixtures. During fire, gases hazardous to health may be formed.

and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

so without risk.

**Specific methods** 

Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards** Combustible liquid.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Immediately evacuate personnel to safe areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** 

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid

discharge into drains, water courses or onto the ground.

Material name: S-3451 SOLVENT BLEND 981 Version #: 01 Issue date: 06-03-2014

Product: Attack!® Super Off Emergency Phone: 317-781-4400

## 7. Handling and storage

## Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. Do not get this material in contact with skin. Do not taste or swallow. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Avoid release to the environment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep in an area equipped with sprinklers.

## 8. Exposure controls/personal protection

# **Occupational exposure limits**

Components	Туре	Value	
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3	
		50 ppm	
Naphthalene (CAS 91-20-3)	PEL	50 mg/m3	
		10 ppm	
<b>US. ACGIH Threshold Limit Valu</b>	es		
Components	Туре	Value	
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm	
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm	
Naphthalene (CAS 91-20-3)	STEL	15 ppm	
	TWA	10 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3	
		25 ppm	
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3	
		5 ppm	
Naphthalene (CAS 91-20-3)	STEL	75 mg/m3	
·		15 ppm	
	TWA	50 mg/m3	
		10 ppm	

## **Biological limit values**

<b>ACGIH Biological</b>	<b>Exposure Indices</b>
Components	Value

Components	Value	Determinant	Specimen	Sampling Time	
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*	

<sup>\* -</sup> For sampling details, please see the source document.

### **Exposure guidelines**

**US - California OELs: Skin designation** 

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies** 

2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

**US - Tennesse OELs: Skin designation** 

Material name: S-3451 SOLVENT BLEND

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

**US NIOSH Pocket Guide to Chemical Hazards: Skin designation** 

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

981 Version #: 01 Issue date: 06-03-2014

Product: Attack!® Super Off Emergency Phone: 317-781-4400

## US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

**Appropriate engineering** 

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear eye/face protection. Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves.

Skin protection

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

**General hygiene** considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** Clear. **Physical state** Liquid. **Form** Liquid. Color Colorless. Odor Typical Solvent.

**Odor threshold** Not available. Not available. pН

Melting point/freezing point Initial boiling point and

boiling range

-94 °F (-70 °C) estimated 336.2 °F (169 °C) estimated

150.8 °F (66.0 °C) Lowest Flashing component Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower 0.8 % estimated

(%)

Flammability limit -

upper (%)

10.6 % estimated

**Explosive limit - lower** 

(%)

Not available.

**Explosive limit - upper** 

Vapor pressure

Not available.

(%)

0.77 hPa 1 hPa = 0.75006 mmHg estimated

Not available. Vapor density Relative density Not available.

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

471.2 °F (244 °C) estimated **Auto-ignition temperature** 

**Decomposition temperature** Not available. Not available. **Viscosity** 

Other information

Density 0.91 g/cm3 estimated Combustible IIIA Flash point class **Percent volatile** 96.56 % estimated

Pounds per gallon 7.5 lb/gal Specific gravity 0.9

Material name: S-3451 SOLVENT BLEND 981 Version #: 01 Issue date: 06-03-2014

SDS US

Emergency Phone: 317-781-4400

VOC (Weight %) 96.56 % estimated

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Suitable precautions should be utilized

if using this product at temperatures above the flash point. Contact with incompatible materials.

**Incompatible materials** Strong oxidizers and strong acids.

**Hazardous decomposition** 

products

No hazardous decomposition products are known if stored and applied as directed.

## 11. Toxicological information

# Information on likely routes of exposure

Ingestion Harmful if swallowed.

Inhalation Prolonged inhalation may be harmful.

Skin contact Toxic in contact with skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

**Eye contact** Direct contact with eyes may cause temporary irritation. Symptoms related to the Direct contact with eyes may cause temporary irritation.

physical, chemical and toxicological characteristics

### Information on toxicological effects

**Acute toxicity** Toxic in contact with skin. Harmful if swallowed. Expected to be a low hazard for usual industrial

or commercial handling by trained personnel.

**Test Results** Components **Species** 

1,2,4-Trimethylbenzene (CAS 95-63-6)

**Acute** 

Dermal

LD50 Rabbit > 3160 mg/kg

Inhalation

Rat LC50 > 2000 ppm, 48 Hours

Oral

LD50 Rat 6 q/kg

2-Butoxyethanol (CAS 111-76-2)

**Acute** 

Dermal

LD50 Rabbit 400 mg/kg

Inhalation

LD50

LC50 Mouse 700 ppm, 7 Hours Rat 450 ppm, 4 Hours

Guinea pig

Rat

Oral

Mouse 1.2 g/kg Rabbit 0.32 g/kg

Other

Material name: S-3451 SOLVENT BLEND

LD50 Mouse 1130 mg/kg

> Rabbit 280 mg/kg Rat 340 mg/kg

981 Version #: 01 Issue date: 06-03-2014 Product: Attack!® Super Off

SDS US 5/9

1.2 g/kg

560 mg/kg

Components Species		Test Results	
Naphthalene (CAS 91-20-3)			
Acute			
Dermal			
LD50	Rabbit	> 2 g/kg	
	Rat	> 20 g/kg	
Oral			
LD50	Guinea pig	1200 mg/kg	
	Rat	490 mg/kg	
Other			
LD50	Mouse	100 mg/kg	

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation. irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

Naphthalene (CAS 91-20-3) 2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Naphthalene (CAS 91-20-3) Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

**Aspiration hazard** Not available.

**Chronic effects** Prolonged inhalation may be harmful. May be harmful if absorbed through skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Components		Species	Test Results
1,2,4-Trimethylbenzer	ne (CAS 95-63-6)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	7.19 - 8.28 mg/l, 96 hours
2-Butoxyethanol (CAS <b>Aquatic</b>	111-76-2)		
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
Naphthalene (CAS 91-	20-3)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Pink salmon (Oncorhynchus gorbuscha)	1.11 - 1.68 mg/l, 96 hours

Material name: S-3451 SOLVENT BLEND 981 Version #: 01 Issue date: 06-03-2014 **Components Species Test Results** 

Nonylphenol Ethoxylate (CAS 9016-45-9)

**Aquatic** 

EC50 Crustacea Water flea (Daphnia magna) 12.2 mg/l, 48 hours Fish LC50 Bluegill (Lepomis macrochirus) 1 - 1.8 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

Partition coefficient n-octanol / water (log Kow)

2-Butoxyethanol 0.83 3.3 Naphthalene

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and

> its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Dispose in accordance with all applicable regulations.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

# 14. Transport information

**DOT BULK** 

NA1993 **UN number** 

Proper shipping name Combustible Liquid, N.O.S. (Petroleum Distillates, Ethylene Glycol Monobutyl Ether)

Packing group III **ERG** code 128

**DOT NON-BULK** 

Not regulated as dangerous goods.

#### 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

2-Butoxyethanol (CAS 111-76-2) Listed. Naphthalene (CAS 91-20-3) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312** Yes

**Hazardous chemical** 

SARA 313 (TRI reporting)

Material name: S-3451 SOLVENT BLEND

Chemical name	CAS number	% by wt.
1,2,4-Trimethylbenzene	95-63-6	0.1-10

981 Version #: 01 Issue date: 06-03-2014

Product: Attack!® Super Off Emergency Phone: 317-781-4400

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

## SARA 313 (TRI reporting)

 Chemical name	CAS number	% by wt.	
2-Butoxyethanol	111-76-2	0.1-10	
Ethylene Glycol	107-21-1	0.1-10	
Naphthalene	91-20-3	0.1-10	

### Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Naphthalene (CAS 91-20-3)

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

#### **US state regulations**

#### **US. Massachusetts RTK - Substance List**

1,2,4-Trimethylbenzene (CAS 95-63-6) 2-Butoxyethanol (CAS 111-76-2) Naphthalene (CAS 91-20-3)

## **US. New Jersey Worker and Community Right-to-Know Act**

 1,2,4-Trimethylbenzene (CAS 95-63-6)
 500 LBS

 2-Butoxyethanol (CAS 111-76-2)
 500 LBS

 Naphthalene (CAS 91-20-3)
 500 LBS

## **US. Pennsylvania RTK - Hazardous Substances**

1,2,4-Trimethylbenzene (CAS 95-63-6) 2-Butoxyethanol (CAS 111-76-2) Heavy Aromatic Naphtha (CAS 64742-94-5)

Naphthalene (CAS 91-20-3)

#### **US. Rhode Island RTK**

1,2,4-Trimethylbenzene (CAS 95-63-6) 2-Butoxyethanol (CAS 111-76-2) Naphthalene (CAS 91-20-3)

## **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Naphthalene (CAS 91-20-3) Listed: April 19, 2002

## **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 06-03-2014

Version # 01

981 Version #: 01 Issue date: 06-03-2014

Product: Attack!® Super Off

Emergency Phone: 317-781-4400

# **Disclaimer**

This information is based on data available to us and is accurate and reliable to the best of our knowledge at the time of printing. However, no warranty is expressed or implied regarding the accuracy or completeness of the information contained herein. Final determination of the suitability of this material for the use contemplated is the sole responsibility of the user. Buyer assumes all risk and liabilities. Buyer accepts and uses this material on these conditions.

981 Version #: 01 Issue date: 06-03-2014

Material name: S-3451 SOLVENT BLEND