



PYRAMEX
Perform At Your Peak™

Cortez® ANSI CE



CO-INJECTED
TEMPLES



RUBBER
NOSEPIECE

Durable co-injected temples

Ribbed cushioned nosepiece



| Part No. | Black Temples |
|-------------|---------------|
| SB3610S ●● | Clear |
| SB3610ST ●● | AF Clear H2X |
| SB3620S ●● | Gray |
| SB3680S ●● | I/O Mirror |



| Part No. | Apple Temples |
|-----------|---------------|
| SA3610S ● | Clear |



| Part No. | Gray Temples |
|-----------|--------------|
| SG3610S ● | Clear |
| SG3620S ● | Gray |



| Part No. | Orange Temples |
|-----------|----------------|
| S03610S ● | Clear |
| S03620S ● | Gray |



| Part No. | Navy Temples |
|-----------|---------------|
| SN3610S ● | Clear |
| SN3660S ● | Infinity Blue |

There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●●) standards.



Cortez®

General Specifications

- Weight: 23 gm
- PD: 68 mm
- Bridge: 12 mm
- Lens base: 9.5 curve
- Lens size diagonal: 70 mm
- Lens size vertical: 43 mm
- Lens thickness: 2.20 mm
- Overall length (lens - tip): 157 mm
- Overall width (hinge - hinge): 137 mm
- Closest point between temple tips: 73 mm
- Closest point between lens: 15.5 mm

Materials

- Lens: polycarbonate
- Temples: polycarbonate & thermoplastic elastomers (TPE)
- Hinge: polycarbonate
- Screw: stainless steel
- Side shields: polycarbonate
- Nosepiece: polycarbonate & polyvinyl chloride (PVC)

| Part No. | Lens Markings | Frame Markings |
|----------|-----------------|----------------|
| SA3610S | P Z87 + U6 | P Z87 + |
| SB3610S | P Z87 + U6 | P Z87 + |
| SB3610ST | P Z87 + U6 | P Z87 + |
| SB3620S | P Z87 + U6 L2.5 | P Z87 + |
| SB3680S | P Z87 + U6 L1.7 | P Z87 + |
| SG3610S | P Z87 + U6 | P Z87 + |
| SG3620S | P Z87 + U6 L2.5 | P Z87 + |
| S03610S | P Z87 + U6 | P Z87 + |
| S03620S | P Z87 + U6 L2.5 | P Z87 + |
| SN3610S | P Z87 + U6 | P Z87 + |
| SN3660S | P Z87 + U6 L1.3 | P Z87 + |

Lens Marking Symbols

- P: Manufacturer's mark
- Z87: ANSI standard for eye and face protection devices
- +: High impact
- UV Filter Transmittance
- U6: .01% max effective far UV • .1% max near UV
- Visible Light Filters
- L1.3: 85% max visible light
- L1.7: 55% max visible light
- L2.5: 29% max visible light

Frame Marking Symbols

- P: Manufacturer's mark
- Z87: ANSI standard for eye and face protection devices
- +: High impact



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967