

MICROFLEX®

▲ FREEFORM® SE



BLUE
NITRILE
NON-STERILE
AMBIDEXTROUS
TEXTURED FINGERS
BEADED CUFF
FOR SINGLE USE ONLY
NON-LATEX

POWDER-FREE EXAMINATION GLOVES

If your light to mid-duty tasks demand reliable protection, FreeForm® SE is the glove you need. The unique combination of strength and comfort makes FreeForm® SE gloves a top choice for a variety of jobs.

- Best for light to mid-duty tasks that need reliable protection
- Non-stick properties resists tape and adhesives
- Textured fingertips for enhanced grip
- Meets or exceeds NFPA requirements



STRONG YET COMFORTABLE FOR EXTENDED USE

PRODUCT CODE		PACKAGING	
XS	FFS-700-XS	100	Gloves/Box
S	FFS-700-S	10	Boxes/Case
M	FFS-700-M		
L	FFS-700-L		
XL	FFS-700-XL		

GLOVE PROFILE		ASTM D 6319	FREEFORM® SE
Length	<i>mm (inches)</i>	min. 220 (8.7)	243 (9.6)
Cuff Thickness	<i>mm (mils)</i>	n/a	0.07 (2.8)
Palm Thickness	<i>mm (mils)</i>	min. 0.05 (2.0)	0.09 (3.5)
Finger Thickness	<i>mm (mils)</i>	min. 0.05 (2.0)	0.13 (5.1)
Tensile Strength	<i>Before Aging</i>	min. 14	32
	<i>After Aging</i>	min. 14	31
Elasticity/Elongation	<i>Before Aging</i>	min. 500	500
	<i>After Aging</i>	min. 400	400
Pinhole Defect Rate*	<i>(AQL)</i>	max. 2.5	1.5

* Pinhole Defect Rate is FDA minimum requirement.



RECOMMENDED INDUSTRIES